


Specification Sheet

-LED Vapor Tight Fixture-





-LED Vapor Tight Fixture-

DESCRIPTION

The HY series is a next generation LED Vapor Tight Fixture that provides maximum light output with durable construction. It is ideal for featuring a one piece polycarbonate housing and lens. The HY was designed to meet or exceed IES recommended foot-candle levels at installed heights for parking garages. Ideal for utility lighting, parking garages and stairwells; where meeting applicable building and safety codes is required. the LED vapor light is super easy to set up and instantly provides full brightness. We oer fvewattage variation with clear and frosted covers distribution of up to130lm/w.

FEATURE

- Ip66. water tight and dust tight
- Available in 2 foot, 4 foot and 8 foot
- PCB with 4KV withstand voltage tating, and polycarbonate housing with 5VA rated fire resistance rating
- Full-length, gasketed polycarbonate lens and single poece noncorrosive polycarbonate body,
- Option: available with emergency backup kit/motion sensor
- WARRANTY--5-year limited warranty

APPLICATION

• Parking garages, docks, subway station; canopy; walk-in refrigerators, awning, outdoor application..




Specifications						
Model No.	HY -2FT-VT-20W3CCT(XX)	HY -4FT-VT-3W3CCT(XX)	HY -8FT-VT-3W3CCT(XX)			
Power:	20W	40/30/20W	80/60/40W			
Size:	2ft	4ft	8ft			
Input Voltage:	120-277 VAC/120-347VAC					
Dimming	0-10V Dimmable					
Lumens	2600LM	5200LM/3900LM/2600LM	10400LM/7800LM/5200LM			
Protection Rating	Ip66					
Power Factor:	90.9					
Beam Angle	120°					
CRI:	>80					
Working Life:	Lumen Maintenance over 70% @ 50,000+ Hours					
Oper. Temperature	-13°F ~+113°F / -25°C ~+45°C					
Certification	DLC Premium / ETL					




-LED Vapor Tight Fixture-

PRODUCT DIMENSIONS



4ft Front View


Side View






2ft Front View

Side View



PHOTOMETRIC REPORT





-LED Vapor Tight Fixture-


ORDERING GUIDE							
Package Information							
Model No.	HY -2FT-VT-20W3CCT(XX)	HY -4FT-VT-3W3CCT(XX)	HY -8FT-VT-3W3CCT(XX)				
Size	2ft	4ft	8ft				
Qty/Pack	6 PCS	6 PCS	4 PCS				
Package Size	690X245X280mm 27.2"X9.65"X11.02"	1290X245X280mm 50.8"X9.65"X11.02"	2450X245X200mm 96.5"X9.65"X7.87"				
Package Weight	9 kg/19.84 lbs	15.1 kg/33.29 lbs	24 kg/52.91 lbs				
Package CBM	0.047334	0.088494	0.12005				
40GP Capacity	~7350 PCS	~3930 PCS	~1930 PCS				
40HQ Capacity	~8610 PCS	~4610PCS	~2260 PCS				
45HQ Capacity	~9880 PCS	~5280 PCS	~2590 PCS				

ORDERING CODE DEFINITION

Company Code	Size	Product	Watt	ССТ
НҮ	2ft 4ft 8ft	VT: LED Vapor Tight Fixture	2ft:20W 4ft:40/30/20W 8ft:80/60/40W	3000/4000/5000K

WARNING

- · The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person
- If the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by the manufacturer or his service agent or a similar gualified person in order to avoid a hazard
- Maximum number /power of fittings for loop in/ out power option: 10 units/ 750W



using clips provided

INSTALLATION INSTRUCTION

